


# NPU 1300

## Negative Pressure Units

The NPU 1300 is one of the smallest units in our range. It is a portable, lightweight unit designed to provide a nominal airflow of 1300 m<sup>3</sup>/hr, which meets HSE requirements. It is typically used in the controlled removal of asbestos-containing materials and is ideally suited to domestic environments and hard to access areas where a smaller machine is more practical.

Filtering contaminated air is critical to controlling the spread of hazardous substances. SMH's air filtration units are designed to tackle a wide range of contaminants, including asbestos, smoke, dust, pollen, bacteria, fungi and viruses.

Air is drawn into the unit by a powerful motor and through a series of filters with each filter operating with a higher efficiency than the last. This is a two-stage process: a pleated pre-filter which removes all larger particulates from the air, down to 10µm in diameter, and a secondary filter, typically a HEPA (High Efficiency Particulate Air) filter which captures smaller particulates. A H14-class HEPA filter captures at least 99.995% of all particulates around 0.3µm in diameter, and is even more efficient at capturing particulates <0.1µm and >1µm. The filtered air is then vented to the environment.



### At a glance

- All units conform to the high specification of British Standards for equipment used in the controlled removal of asbestos-containing materials as well as a range of other relevant standards
- Sturdy and light, with handles for easier lifting
- Polypropylene housing which is easy to clean
- Quick and easy pre-filter replacement while in situ
- Efficient two-stage air filtration with a pre-filter and a HEPA filter

### Available to buy or hire – contact your nearest branch

Leeds  
 0113 279 9003  
 leeds@smhproducts.com

London  
 0127 781 0035  
 london@smhproducts.com

Bristol  
 0117 403 5830  
 bristol@smhproducts.com

Glasgow  
 0141 556 6600  
 glasgow@smhproducts.com

Romsey  
 0179 452 4000  
 romsey@smhproducts.com

St Helens  
 0174 426 660  
 sthelens@smhproducts.com

Washington  
 0191 456 6002  
 washington@smhproducts.com

Birmingham  
 0121 328 6000  
 birmingham@smhproducts.com

# Technical Data

## Specifications

Case	Case material	Polypropylene
	Case colour	Grey
	Weight (kg)	31
Electric	Voltage (V)	110
	Mains frequency (Hz)	50
	Supply (no. of phases)	1
	Power, input, max. (W)	1000
	Current, nominal (A)	14
	Electrical protection	16A MCB
	Isolation on/off switch	✓
Airflow & Filters	Nominal airflow (m <sup>3</sup> /hr)	1300
	Nominal airflow (CFM)	765
	Noise level, max. (dBA) Measured at 1m distance without ducting	86
	Differential pressure gauge (Pa)	0-1250
	Pre-filter dimensions (mm)	372x372x98
	HI4 HEPA filter dimensions (mm)	381x381x150
Dimensions	Case length, A (mm)	607
	Case width, B (mm)	550
	Case height, C (mm)	615
	Floor clearance height, D (mm)	107
	Exhaust outlet diameter, E (mm)	200
	Exhaust outlet depth, F (mm)	70
	Cover plate width, G (mm)	505
	Cover plate height, H (mm)	505

## Optional Extras & Accessories

Extras	Hour meter	✓
	Airflow monitor	✓
	Variable speed control	✓
Accessories	Spigot plate	✓
	Roving filter	✓

## Certification

- All units come PAT and DOP tested;
- The NPU's comply with BS EN 8520-2:2009 Equipment used in the controlled removal of asbestos-containing materials (ACMs);
- The NPU's HEPA filter complies with BS EN 1822-1;
- All appliances comply with BS EN 60335-2-69 Household and similar appliances;
- The units are manufactured at an ISO 9001 quality assured site.

## Technical Drawing

