



*UK version comes with 32 amp plug.

HUSQVARNA BGS 250

A HEAVY-DUTY SINGLE-DISC FLOOR GRINDER FOR SURFACE PREPARATION

The heavy-duty BGS 250 is a single-disc concrete grinder specially designed for small to medium-sized professional surface preparation applications. The machine's tailored disc tooling system enables low vibrations and high productivity. The adjustable handle contributes to a comfortable operating experience and, together with the machine's low weight, also makes the BGS 250 easy to transport. The BGS 250 can be plugged in and started with the push of a button.

FEATURES



AGGRESSIVE GRINDING

The single grinding head distributes all the machine's pressure to be distributed onto the small diameter of the tailored diamond disc. This, together with the adjustable wheel settings, results in aggressive grinding.



EFFICIENT DUST MANAGEMENT

This grinder is equipped with a 51 mm diameter dust hose connection for minimised dust exposure on the job site.



PLUG & GRIND

With this single phase single disc grinder you just plug it in and press start to begin grinding.



EASY TO TRANSPORT

The handle can be folded for easy transportation.



EFFECTIVE DUST PICKUP

Thanks to an integrated dust fan.

OPTIMAL PRODUCTIVITY

Adjustable wheel settings to change grinding pressure.

TECHNICAL DATA HUSQVARNA BGS 250

Art.no: 970 64 78-02 FLOOR GRINDER BGS 250 | 1x110 V | 1.1 kW | 50 Hz | UK

PRODUCT DATA

Phases 1 ph Voltage 110 V Rated current. 11 A Plug 32 A Frequency 50 Hz Grinding width 250 mm Number of grinding discs 1 Grinding disc speed max 800 rpm Type of operation Push	Output power	1.1 kW
Rated current. 11 A Plug 32 A Frequency 50 Hz Grinding width 250 mm Number of grinding discs 1 Grinding disc speed max 800 rpm	Phases	1 ph
Plug 32 A Frequency 50 Hz Grinding width 250 mm Number of grinding discs 1 Grinding disc speed max 800 rpm	Voltage	110 V
Frequency 50 Hz Grinding width 250 mm Number of grinding discs 1 Grinding disc speed max 800 rpm	Rated current.	11 A
Grinding width 250 mm Number of grinding discs 1 Grinding disc speed max 800 rpm	Plug	32 A
Number of grinding discs 1 Grinding disc speed max 800 rpm	Frequency	50 Hz
Grinding disc speed max 800 rpm	Grinding width	250 mm
	Number of grinding discs	1
Type of operation Push	Grinding disc speed max	800 rpm
	Type of operation	Push

DIMENSIONS

Product size length	1,188 mm
Product size width	505 mm
Product size height	936 mm
Weight	62 kg

RELATED TOOLS AND PRODUCTS



HUSQVARNA ELITE-GRIND DISC T-REX

Aggressive 250 mm/10" diameter grinding disc equipped with PCD (polycrystalline diamond) claws, specifically designed for removing thick layers (1-2 mm) of soft contaminants such as glue and coatings.



HUSQVARNA VARI-GRIND STAR X

An agressive 250 mm/10" diameter grinding disc designed for removal on harder concrete floors.



HUSQVARNA DE 130 H DUST EXTRACTOR

High-productive single-phase H/ HEPA dust extractor designed for demanding applications such as floor preparation, grinding, shaving, scarifying, shot blasting, and together with larger handheld tools.



HUSQVARNA DE 120 H DUST EXTRACTOR

A versatile H-class dust extractor is compact and easy to transport, yet powerful. It is designed for use with larger hand-held power-tools, floor and hand grinders, shotblasters, scarifiers and more.

