

Hasflex Aluminium Flexible Ducting



Hasflex MU Aluminium Uninsulated Flexible Ducting

Application

HASFLEX MU is a range of fully flexible uninsulated aluminium/polyester laminated ducting, which has been specially designed for the HVAC Market. Due to its flexibility it is easy to connect to either round or oval ducting.

Construction

HASFLEX MU is multi-ply reinforced aluminium and polyester laminated ducting with an encapsulated high tensile steel wire helix.

Advantages

- Supplied in standard 10 metre length, compressed to 0.6 metre.
- Individually boxed.
- Easy to connect to either round or oval ducting.
- No special tools required for cutting or fixing.
- In the event of a fire no toxic gases are emitted.
- The products have been successfully fire resistance tested to BS476 parts 6, 7 and 20.



Technical data

Construction Material	Reinforced Aluminium/Polyester
Wirepitch	24mm
Diameter range (mm)	80-610
Temperature range	-30/+140
Maximum air velocity	30m/sec
Max.positive working pressure	2500 Pa
Standard length	10 metre
Packing	Individual box of 0.6 metre
Clamping	Hasflex Lightning Band, Stainless Steel Clamps, Nylon Clamps or Quick Release Clamps

Head Office Heath Mill Road, Wombourne, Wolverhampton, West Midlands WV5 8AP

Head Office 01902 895161
Wolverhampton Branch 01902 895161
Hailsham Branch 01323 847910

London Branch 020 8803 9622
Rochester Branch 01634 672730
Stoke Branch 01782 274000

Bury Branch 0161 796 8226
Nottingham Branch 0115 979 4527
Eastleigh Branch 02380 612954

sales@has-vent.co.uk www.has-vent.co.uk